

s h a p e



Hudevad P100



output table

HUDEVAD
s h a p e

Radiator data P100

	Depth = 100	Depth = 184	Depth = 268
n	1.45	1.47	1.50
K_m	1.25	2.27	3.03
W/m 75°/65°/20°C	367 W	717 W	1088 W
W/m 55°/45°/20°C	174 W	336 W	501 W

Output in watts at a temperature set of 90° / 70° / 20°

Length (mm)	Depth = 100	Depth = 184	Depth = 268
710	337 W	660 W	1006 W
810	384 W	752 W	1148 W
910	432 W	845 W	1290 W
1010	474 W	929 W	1417 W
1110	526 W	1031 W	1573 W
1210	574 W	1124 W	1715 W
1310	621 W	1217 W	1857 W
1410	669 W	1310 W	1998 W
1510	716 W	1403 W	2140 W
1610	763 W	1495 W	2282 W
1710	811 W	1588 W	2424 W
1810	858 W	1681 W	2565 W
1910	906 W	1774 W	2707 W
2010	953 W	1867 W	2849 W
2110	1001 W	1960 W	2991 W
2210	1048 W	2053 W	3132 W
2310	1095 W	2146 W	3274 W
2410	1143 W	2239 W	3416 W
2510	1190 W	2331 W	3558 W

Outputs measured with flow at A and return at D